

Photo non contractuelle / Non-contractual photo



FC1600E-*



16 levels - 400x600 mm - fixed trolley

- Max temperature : 270°C
- Pitch : 88 mm
- Stainless steel frame
- Monobloc
- Glass door
- Lighting
- Trolley not supplied
- Timer
- General switch
- Steam generator
- 3 heating fans
- Turbine speed control
(FCxE-E et FCxE-P)
- 400/50Hz/3



- Options :
- 16 level trolley
 - Hood
 - 60Hz

Possibility of reducing the spacing from 88 to 70mm to obtain 20 levels
20-level trolley

16 niveaux - 400x600 mm - chariot fixe

Température max : 270°C

Pas de 88 mm

Inox

Monobloc

Porte vitrée

Éclairage

Chariot non fourni

Minuterie

Interrupteur général

Humidificateur

3 turbines de chauffage

Régulation de la vitesse de turbine

(FCxE-E et FCxE-P)

400/50Hz/3


Options :

Chariot 16 niveaux

Hotte

60Hz

Possibilité de réduire l'espace entre les glissières de 88 à 70mm pour obtenir 20 niveaux
Chariot 20 niveaux



| | FC1600E-M | FC1600E-E | FC1600E-P |
|---|--------------------------------|----------------------------|--------------|
| Tableau de commandes Control panel | Electromécanique Mechanical | Electronique Electronic | Programmable |
| Dimensions | | | |
| Largeur / Width mm | 925 | | |
| Profondeur / Depth mm | 1695 | | |
| Hauteur / Height mm | 2150 | | |
| Poids / Weight | | | |
| Kg | 415 | | |
| Puissance / Power | | | |
| kW | 23.7 | | |